

ANAEROBICS

Description	Packing	Certification
Screwlock : Ideal for thread locking small screws from loosening under vibration	50mlx12/ 250mlx6	WRAS BS 6920-1:2000
Nutlock : Ideal for thread locking small screws from loosening under vibration	50mlx12/ 250mlx6	NSF Certified
Studlock : Ideal for fastener up to 1" in dia.It has high strength, permanent and eliminates need for double nutting and welding.	50mlx12/ 250mlx6	WRAS BS 6920-1:2000
High Temp Studlock : Ideal for fastener up to 1" in dia.It has high strength , permanent and eliminates need for double nutting and welding.	50mlx12/ 250mlx6	WRAS BS 6920-1:2000
Penetrating Thread Locker : Penetrates threads by capillary action	50mlx12/ 250mlx6	R-46082B Type III Grade R'
Shaft Retainer : It retains bearings into pump housings.	50mlx12/ 250mlx6	WRAS BS 6920-1:2000
High Temp Retaining Compound : Ideal to fill gaps up to 0.01" dia clearance.	50mlx12/ 250mlx6	WRAS BS 6920-1:2000
Very High Retainer : Ideal to fill gaps up to 0.01" dia clearance.It is excellent retaining, sealing and thread locking compound.	50mlx12/ 250mlx6	NSF Certified
Bearing Retainer : Ideal to fill gaps up to 0.008" dia clearance.It is high performance, controlled strength, versatile bearing compound.	50mlx12/ 250mlx6	WRAS BS 6920-1:2000
Hydraulic Sealant : It is designed for bonding of cylindrical fitting parts.It has low viscosity with medium strength sealing property	50mlx12/ 250mlx6	WRAS BS 6920-1:2000
Pipe Thread Sealant with PTFE : It is designed for the locking and sealing of metal tapered threads and fittings	50mlx12/ 250mlx6	WRAS BS 6920-1:2000
Pipe Sealant for Coarse Threads : It is designed for the locking and sealing of metal tapered threads and fittings	50mlx12/ 250mlx6	WRAS BS 6920-1:2000

