



# SOUDAL COLOR SPRAY

Revision: 1/04/2024

Page 1 of 2

## Technical Data

Basis	Pure Acrylic Polymer + Pigment + Solvents + Standard CFC Free Gas
Specific Gravity (g/cm <sup>3</sup> )	0.90 ± 0.05
Viscosity on Zahn Cup (sec)	30.00 ± 5
Fineness of Grind (Microns)	2-5
Solid Content (%)	23.00 ± 5
Drying Time (mins, @ 15°C-45°C)	Approx. 2 – 7
Gloss (GU)	> 85
Dry Opacity (%)	99
Lead Content (%)	< 0.0005
Appearance of Dried Film	Smooth finish free from brush marks, wrinkling, running, sagging, or orange peel
Flexibility & Adhesion (Mandrel Test)	Pass - 5 mm
Scratch Resistance	Pass at 800 g of scratch test load
Accelerated Weathering	No Signs of color change, Cracking, Chalking
Coverage	
Dark Color Shades	4-7 Square Meter per liter
Light Color Shades	4-6 Square Meter per liter
Metallic Color Shades	9-11 Square Meter per liter
Service and Application Temp.	+15°C to +45°C

\*These values may vary depending on environmental factors such as temperature, moisture and the type of substrate.

\*\*This information relates to fully cured products.

### Description:

Soudal Color Spray is a high-quality, multi-use acrylic paint designed to provide a bright enamel finish. Suitable for both interior and exterior applications, this versatile spray paint is ideal for a wide range of surfaces and projects. It offers excellent coverage and a durable finish that enhances the appearance of any surface.

### Properties:

- **Good Leveling:** Ensures a smooth and even finish
- **High Spray Rate:** Provides efficient application with excellent coverage
- **Strong Adhesion:** Adheres well to a variety of surfaces, ensuring a long-lasting finish
- **High Coverage:** Offers extensive coverage with fewer coats required
- **Fast Drying:** Dries quickly to a rich color with a high-gloss finish

### Packaging:

Each Soudal Color Spray can has a volume of 400 ml. 12 cans are packed in each carton.

### Color Shades:

- **Standard Colors:** Wide range of standard colors available
- **Matte Shades:** Available in matte finishes for a subdued look
- **Metallic Shades:** Offers metallic finishes for a reflective, shiny appearance
- **Fluorescent Shades:** Bright, fluorescent colors for high visibility applications

### Applications:

- **Surfaces:** Suitable for wood, metal, glass, ceramic, plastering, masonite, and more.
- **Objects:** Ideal for doors, chairs, furniture, frames,

**Remark:** The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.

**Soudal India Pvt. Ltd.**

Plot No. 200, Sec. 4, Phase - II, Growth Centre, Bawal, Dist. Rewari, Haryana - 123501 (India)  
info@soudal.in | www.soudal.in | +91 8010-114-114

## Soudal Color Spray

Revision: 1/04/2024

Page 2 of 2

knick-knacks, radiators, and many other objects.

- **Removal:** Product can be removed with synthetic thinner or acetone.



### Shelf Life and Storage:

- **Storage:** Store in a cool, dry location in unopened containers below 25°C. Do not place in direct sunlight or near any heat, sparks, or flame sources. A maximum height of 6.7 ft (2 meters) should be maintained for pallets containing spray paint cartons.
- **Shelf Life:** 36 months from the date of manufacturing. Storage outside specified parameters may reduce the shelf life.

### Application Method:

- **Surface Preparation:** Clean the surface thoroughly to remove dirt, grease, oil, soapy film, rust, moisture, etc. The application environment should be moisture-free and well-ventilated.
- **Shaking the Can:** Shake the can vigorously for one minute to ensure color uniformity and better results. Continue shaking occasionally while in use.
- **Spraying Distance:** Spray from a distance of 30 cm (12 inches) away from the object. Ensure the temperature is not below 20°C (68°F).
- **Coating:** For best results, apply two thin coats instead of one heavy coat. Allow a coating time interval of 3-5 minutes between each coat.
- **Preventing Clogging:** While spraying, invert the can for a second to remove excess paint from the spray head and prevent clogging.

### Handling Precautions:

- Do not use near flames, sparks, direct sunlight, heat, etc.
- Pressurized container. Do not expose to temperatures exceeding 50°C.
- Do not puncture or incinerate the can.
- For safe handling information, refer to the Material Safety Data Sheet (MSDS) of this product.

**Remark:** The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.

**Soudal India Pvt. Ltd.**

Plot No. 200, Sec. 4, Phase - II, Growth Centre, Bawal, Dist. Rewari, Haryana - 123501 (India)  
info@soudal.in | www.soudal.in | +91 8010-114-114