



THE STRESS FREE BONDING



Proudly made in India

TECHNICAL DATA SHEET

ESSRBOND EB 323 (Multi Purpose Siliconized Sealant)

EB/TDS/7080, Date : March - 2023

DESCRIPTION

ESSRBOND EB 323 Multipurpose is a siliconized acrylic sealant that is designed for filling gaps such as gaps behind basins, gaps near switch boards, gaps near window frames and many other gap filling purposes.

FEATURES

- ◆ Multipurpose
- ◆ Economical
- ◆ Non-sag, Paste consistency.
- ◆ Areas of use
- ◆ Gap Filling
- ◆ Gap filling in bathrooms
- ◆ Gap filling in interior and exterior applications, where large amount of movement is not expected



TECHNICAL PROPERTIES

PROPERTIES	RESULTS
Appearance	Smooth Paste
Non Volatile Matter	> 80.00 %
Density	1.65 ± 0.05
Viscosity (Spindle no. 7/20 rpm)	1,00,000 - 2,00,000 cps
Application Temperature	+5°C to 35°C

DIRECTION FOR USE

- ◆ Remove dust, grease, moisture & old caulk.
- ◆ Use backer rod if joint size exceed 12 mm.
- ◆ Mask both sides of joint for neat & clean application
- ◆ Cut nozzle of cartridge desired bead size. Load sealant cartridge in caulking gun.
- ◆ Place nozzle on cartridge and apply sealant into gap.
- ◆ Wipe hand and tools thoroughly before washing. Will become tack free in 30 min. Normally cures in 24-28 hrs
- ◆ Smooth or "tool" bead if needed.
- ◆ Remove masking tape immediately after finishing.
- ◆ Clean with white spirit immediately after use finish with tool before skinning.



THE STRESS FREE BONDING



Proudly made in India

TECHNICAL DATA SHEET

ESSRBOND EB 323 (Multi Purpose Siliconized Sealant)

EB/TDS/7080, Date : March - 2023

PRECAUTION

- ◆ Surface must be clean, dry and free of grease and oil. Avoid eye contact.
- ◆ Ensure right safety wares are worn when applying
- ◆ In case of eye contact, flush with water for 15 min and if problem persists, call a physician.

HEALTH & SAFETY

Keep out of reach from children. Before handling, read both the product and material safety data sheet for detailed use and health information.

STORAGE

Store in a cool, dry place. Away from direct sunlight and moisture. Storage temperature to be below and 30°C.

SHELF LIFE

24 months from date of manufacturing in unopened conditions.

PACKING

290 ml Cartridge 48 pcs in a box.



NOTE

The company's products are sold subject to the Company's standard terms and conditions of sale. Products are warranted against defective materials and workmanship. The company makes every effort to ensure that all the information, recommendations or the specifications provided by it are accurate and true. However as the company has no control over the conditions of use, it cannot accept any liability, either directly or indirectly regarding the usage of its products. Product specifications are subject to change without prior intimation to users as the products are being continuously upgraded.