

WEATHER PROOFING SILICONE SEALANT

Description:

Weather Proof Sealant is a one part neutral curing sealant which Exhibits high UV resistance and is all weather proof. It is a moisture curing that delivers high performance high elasticity rubber after curing.

Properties: Superior Adhesion to a wide range of building materials including Brickwork and concrete. Does not discolor and is suitable for vertical and Overhead applications. Shore A Hardness of 25-35.

PARAMETER	TEST METHOD	VALUES
Chemical Base		Oxime
Density	(SEL DM 04)	1,4 gr/Cm ³
Tack Free Time	25° C and 50 % Relative Humidity	Approx – 5-8 min.
Hardness	(SEL DM 07)	35 5 SHORE A
Elongation (%)	(SEL DM 05)	> 300
Tensile Strength (MPa)	(SEL DM 05)	1,35
Cure Rate 2.3 mm / 24 Hr.	25o C and 50% Relative Humidity	Approx 18 Hours

Applications: It is used for sealing expansion and control joints in concrete, precast concrete panel joints, brickwork, block work, perimeter sealing around doors and windows and non trafficked floor joints.

Packing: 290 MI Cartridge 25 Pcs in a box
600 MI sausages 20 Pcs in a box.

Colors : White/Black/Grey/Clear

